Roof Outlets


Kompact Balcony Outlets




Offering all the benefits of our standard Balcony Outlets, the Caroflow Kompact Balcony outlet is sized to allow easier, less 'destructive', installation in refurbishment as well as new Balcony installations.

It will still allow various sizes of pipework to drain into the outlet from upper levels.


Available in either LM6 Aluminium Silicon casting alloy to BS EN 1706:2010 for most roof finishes or in leaded gunmetal to BS EN 1982:2008 for use with lead or copper-clad roofs or for connection to copper pipework.




| Order Code | 50/KB0 | 75/KB0 |
|-----------------|--------|--------|
| Pipe size (nom) | 50 | 75 |
| А | 210 | 210 |
| В | 175 | 175 |
| С | 55 | 55 |
| D | 170 | 170 |
| Е | 110 | 110 |
| F | 55 | 55 |
| G | 220 | 220 |
| Н | 60 | 83 |



50mm Kompact Balcony Outlet (Side Elevation) Code 50/KB0




50mm Kompact **Balcony Outlet** (Front Elevation) Code 50/KBO



75mm Kompact **Balcony Outlet** (Side Elevation) Code 75/KBO

Balcony Outlet (Front Elevation) Code 75/KBO



All drawings above are shown 1:5 scale